

RING JOINTS TIPO RX														
DIÂMETRO NOMINAL/ PRESSÃO NOMINAL					DIMENSÕES									Nota 3 PESO
CLASSES					TOLERÂNCIAS	+0,50	+0,50	+0,20	+0,20	+0,15	+0,79	±0,39	E (mm)	Kg
2000	3000	5000	2900*	5000	TIPO RX	OD (mm)	ID (mm)	H (mm)	A (mm)	C (mm)	D (mm)	R1 (mm)		
1.1/2"	1.1/2"	1.1/2"		2.2/16"	RX20	76.20	58.72	19.05	8.74	4.62	3.17	1.52		0.24
2					RX23	93.27	69.45	25.40	11.91	8.45	4.24	1.59		0.52
	2	2			RX24	105.97	82.15	25.40	11.91	6.45	4.24	1.59		0.60
		3.1/8"		3.1/8"	RX25	109.55	92.07	19.05	8.74	4.62	3.17	1.59		0.50
2.1/2"	2.1/2"	2.1/2"			RX26	11.91	88.09	25.40	11.91	6.45	4.24	1.59		0.64
3	3				RX27	118.26	94.44	25.40	11.91	6.45	4.24	1.59		0.68
		3			RX31	134.54	110.72	25.40	11.91	6.45	4.24	1.59		0.78
4	4				RX35	147.24	123.42	25.40	11.91	6.45	4.24	1.59		0.86
		4			RX37	159.94	136.12	25.40	11.91	6.45	4.24	1.59		0.95
5	5				RX39	172.64	148.82	25.40	11.91	6.45	4.24	1.59		1.03
		5			RX41	191.69	167.87	25.40	11.91	6.45	4.24	1.59		1.15
6	6				RX44	204.39	180.57	25.40	11.91	6.45	4.24	1.59		1.23
		6			RX45	221.84	198.02	25.40	11.91	6.45	4.24	1.59		1.34
		8			RX46	222.25	195.27	28.58	13.49	6.68	4.77	1.59		1.66
8	8				RX47	245.28	205.58	41.28	19.84	10.34	6.88	2.29		3.88
		8			RX49	280.59	256.77	25.40	11.91	6.45	4.24	1.5		1.72
10	10				RX50	283.36	250.04	31.75	16.66	8.51	5.28	1.59		2.43
		10			RX53	334.57	310.75	25.40	11.91	6.45	4.24	1.59		2.06
12	12				RX54	337.34	304.02	31.75	15.66	8.51	5.28	1.59		2.92
		14			RX57	391.72	367.90	25.40	11.91	6.45	4.24	1.59		2.42
					RX63	441.73	387.73	50.80	27.00	14.78	8.45	2.29		11.96
16	16				RX65	480.62	458.80	25.40	11.91	6.45	4.24	1.52		3.00
18	18				RX66	457.99	424.67	31.75	16.88	8.51	5.28	2.29		4.25
20	20				RX69	544.12	520.30	25.40	11.91	6.45	4.24	1.52		3.41
					RX70	550.06	510.38	41.28	19.84	10.34	6.88	2.29		9.12
					RX73	596.11	569.13	31.75	13.49	6.68	5.28	1.52		5.27
					RX74	600.88	561.18	41.28	19.84	10.34	6.88	1.59		10.01
			1		RX82	67.87	44.05	25.40	11.91	6.45	4.24	1.59	1.6	0.36
			1.1/2"		RX84	74.22	50.40	25.40	11.91	6.45	4.24	1.59	1.6	0.40
			2		RX85	90.09	83.11	25.40	13.49	6.68	4.24	1.59	1.6	0.40
			2.1/2"		RX86	103.58	73.40	28.58	15.09	8.51	4.77	1.59	2.4	0.81
			3		RX87	113.11	82.93	28.58	15.09	8.51	4.77	1.59	2.4	0.90
			4		RX88	139.29	104.33	31.75	17.48	10.34	5.28	1.59	3.2	1.46
			3.1/2"		RX89	129.77	93.25	31.75	18.26	10.34	5.28	1.59	3.2	3.09
			5		RX90	174.63	134.95	44.45	19.84	12.17	7.41	2.29	3.2	7.75
			10		RX91	286.94	226.58	45.24	30.18	19.81	7.54	2.29	3.2	1.50
8"	8"				RX99	245.67	221.85	25.40	11.91	6.45	4.24	1.52		2.20
		1.3/8"		1.1/8A	RX201	51.46	39.98	11.30	5.74	3.20	1.44	0.51		0.10
		1.11/16"		1.9/16A	RX205	62.31	51.19	11.10	5.56	3.05	1.82	0.51		0.13
		2.9/16"		2.9/16A	RX210	97.64	78.58	19.05	9.53	5.41	3.17	0.78		0.35
		4.1/16"		4.1/16A	RX215	140.89	117.07	25.40	11.91	5.33	4.24	1.52		0.80

NOTAS	
1	TODAS AS MEDIDAS SÃO EM MILIMETROS
2	NA SUPERFICIE DE 23° EM AMBOS OS LADOS DO CHANFRO, A RUGOSIDADE MÁXIMA DEVE SER 63 RMS MÁX.
3	UM FURO DE PASSAGEM DE PRESSÃO "E" SERÁ REALIZADO NO CENTRO
*	FLANGES 2900 API 6B SÃO OBSOLETAS